

PK 202 PATIO GRASS TECHNICAL DATA SHEET

Product reference	- PK202
Production process	- Tufting
Application	- Commercial applications, golf course walkways, multisport use
Composition fibre	- Polypropylene, uv stabilised
Denier / Thickness fibre	- 6600 Dtex
Fibre width	- 12mm
Fibre thickness	- 60 micron
Structure	- Straight, fibrillated
Pile height	- ± 15 mm
Pile weight	- ± 900 gr/m ²
Stitches	- ± 170 lin m
Number of tufts	- ± 35696 m ²
Tufting method	- Linear
Gauge	- 3/16"
Colour	- Green
Colour fastness	- According to DIN 54004, Scale 7
UV Stability	- According to DIN 53387, 6000 hours
Tuft cloth	- Polypropylene, U V Stabilised, ± 134 gr/m ²
Backing	- Latex ± 1100 gr/m ²
Total height	- ± 17 mm
Total weight	- ± 2134 gr/m ²
Water permeability	- $> 5 \times 10^{-4}$ m/s, perforations diameter ± 3 mm, ± 100 mm/m ²
Laying method	- Loose laid on dynamic or bound sub base. Roll joints glued.
Roll width	- ± 2.0 m or 4.0m
Roll length	- 1m multiples, max roll length 30m
Minimum size available	- 2m x 2m
Sand	- $\pm 15 - 20$ kg/m ²



sportsequip.co.uk

The Manor, Tur Langton, Leicestershire LE8 0PJ

tel: 01858 545789 | fax: 01858 545890

e-mail: sales@sportsequip.co.uk | website: www.sportsequip.co.uk

Boyd Sport & Play Ltd trading as sportsequip.co.uk reserve the right to alter or amend specifications without prior notice and cannot be held responsible for any consequences arising out of errors or omissions. sportsequip.co.uk® and Astroturf® are registered trademarks