

### **Compliant Datasheets**

# **Compliant Grass Tiles**

### **SS500 Compliant Grass Tiles Specification & Installation**

Environmentally friendly rubber matting system offering grass reinforcement and a tested, impact absorbing surface.





#### **Features:**

- H.I.C, of 3.0m on grass.
- Impact absorbent.
- Non-slip surface.
- Absorbs shock and noise.
- Excellent durability and comfort.
- Suitable for all weather and extreme temperatures.
- Honeycomb design allows liquid and debris to drain keeping surface dry and clean.

Specification: Rubber Honeycomb Tiles	
Tile Size:	1.5m x 1.0m x 23mm Thick
Tile Weight:	19kg
Colour:	Black

In accordance with the Company's policy of continuous development, Boyd Sport & Play Ltd t/as sportsequip.co.uk reserve the right to alter or amend specifications without prior notice. All statements in this datasheet are made in good faith but the Company will not be held responsible for any consequence arising out of errors or omissions.





# **Compliant Datasheets**

# **Compliant Grass Tiles (continued)**

The area covered is secured in place with the use of galvanised or plastic fixing pins. Allow for 3 no. pins per outer edge of the total carpet area.

#### Installation

#### **Tools Required:**

- Tape Measure.
- Stanley knife.
- Rubber gloves.
- Hammer.
- Grass edge cutter.
- Spade.
- Cable ties.
- Grass Seed.
- Rechargeable drill and 6mm drill bit.
- 3 no. Edge fixing pins at the rate of 3 no. pins per outer edge of tile area.

In accordance with the Company's policy of continuous development, Boyd Sport & Play Ltd t/as sportsequip.co.uk reserve the right to alter or amend specifications without prior notice. All statements in this datasheet are made in good faith but the Company will not be held responsible for any consequence arising out of errors or omissions.





### **Compliant Datasheets**

### **Compliant Grass Tiles (continued)**

#### **Installation Instructions**

- 1. Mark out the area to be covered with the **Compliant Grass Tiles**.
- 2. **Compliant Grass Tiles** can be laid directly onto existing grassed areas. The area should be filled in if uneven with topsoil and be compact.
- 3. Sow grass over this area.
- 4. (OPTIONAL) For soft (boggy) areas lay an open coarse membrane. Leave about 150mm in from the outside edge.
- 5. Now lay out the **Compliant Grass Tiles** over the area to be covered, cutting around any equipment or obstacles if necessary.
- 6. Fasten edges together using cable ties and trim tails.
- 7. Cut into the ground about 75mm deep along the edge of the perimeter area to be covered using a grass edge cutter or similar.
- 8. Roll back the **Compliant Grass Tiles**. Starting about 150mm in from the outside edge of the tiles, use a spade and cut the top turf away in the direction of the 75mm deep cut finishing at the depth. This will leave a wedge shape channel. Continue around the perimeter of the laid tiles.
- 9. Roll the **Compliant Grass Tiles** back and down into the channel and pin the edge through the small holes in the tile and into the ground, Use 1 pin per tile corner and 1 pin midway. You should now have a ramp edge all the way around. Now cover the ramped area with topsoil and seed. Bring the level back up to its original level and flatten.

In accordance with the Company's policy of continuous development, Boyd Sport & Play Ltd t/as sportsequip.co.uk reserve the right to alter or amend specifications without prior notice. All statements in this datasheet are made in good faith but the Company will not be held responsible for any consequence arising out of errors or omissions.

